



形 S8JX シリーズ, 形 S8VM シリーズからの置き換え金具の取り付け方法  
(正面取り付け)



Mounting method of the bracket for replacement  
from model S8JX series, model S8VM series  
(Front mounting)

OMRON






置き換え元機種 Model compatible with the source to be replaced		置き換え金具形式 Model of the bracket for replacement	使用取付穴 Mounting hole for use			
					Type C	
					Type B	
					Type A	
S8JX	S8JX-N015□□ / S8JX-G015□□	S82Y-FSG-F31	a/b	-	-	
	S8JX-N030□□ / S8JX-G035□□		a/b	-	-	
	S8JX-N050□□ / S8JX-G050□□		a/b	-	-	
	S8JX-N100□□ / S8JX-G100□□	S82Y-FSG-F32	a/b	-	-	
	S8JX-N15048 / S8JX-G15048		a/b	-	-	
	S8JX-N15024 / S8JX-G15024		a/b	-	-	
	S8JX-N15012 / S8JX-G15012		a/b	-	-	
	S8JX-N15005 / S8JX-G15005		a/b	-	-	
	S8JX-N300□□ / S8JX-G300□□	S82Y-FSG-F37	-	-	a/b/d/e	
	S8JX-N600□□ / S8JX-G600□□	S82Y-FSG-F39	-	-	a/b/d/e	
	S8JX-P050□□	S82Y-FSG-F31	a/b	-	-	
	S8JX-P100□□	S82Y-FSG-F32	a/b	-	-	
	S8JX-P150□□		a/b	-	-	
	S8JX-P300□□		S82Y-FSG-F36	-	-	a/b/d
	S8JX-P600□□	S82Y-FSG-F38	-	-	a/b/d	
S8VM	S8VM-015□□	S82Y-FSG-F33	-	a/b/d	-	
	S8VM-030□□		-	a/b/d	-	
	S8VM-050□□		-	a/b/d	-	
	S8VM-100□□		S82Y-FSG-F34	-	a/b/d	-
	S8VM-150□□		S82Y-FSG-F35	-	a/b/d	-
	S8VM-300□□		S82Y-FSG-F36	-	-	d/e/f
	S8VM-600□□		S82Y-FSG-F38	-	-	d/e/f

## Type A



推奨締め付けトルク  
Recommended tightening torque  
M3 : 0.54 N·m  
M4 : 1.2 N·m

## Type B



## Type C

